



SIM Card Connector Series

SIM (Subscriber Identity Module) and UIM (Universal Identity Module) cards are widely used in a variety of mobile applications, including, billing, security and number storage purposes in mobile devices. The SIM card parameters are defined by ISO, ETSI and GSM standards.

TE's outstanding technological capability delivers a high comfort for the end customer and great durability and longevity of the SIM connectors. In addition, TE has the ability to fabricate very high volume products in a cost-efficient, lean manufacturing process. The huge array of products, combined with TE's ability to redesign existing products to customer requirements, allow TE to be a reliable source for SIM and UIM card connectors.

Features

- Large portfolio covering several styles and card sizes
- Connectors optimized for reliability (i.e. by spherical contact points increasing hertz stress, pre-loaded contacts and anti retention features in the contacts.)
- The SIM connector series offers the best possible design freedom; many products are even scalable in height within the same form factor
- Best possible applied cost by fully-automated processing

Benefits

- Large, versatile portfolio offers the best product closest to the actual need
- Highly reliable connector technology helps customers reduce production line defect rates - ultimately reducing costs for quality control and service
- Unmatched design freedom creates optimal possibilities for the design engineer to match the device's requirements
- Fully-automated processing leads to stable quality
- Global footprint means enhanced support for all regions

Applications

- Mobile phones
- Tablets
- Personal computers
- Ultrabook
- Data cards
- Portable GSM modems
- Servers

www.te.com/products/SIMCardConnectors

Variety of SIM Card Connectors Portfolio



Push-Pull Type

- Card guidance and card stops provides fixation of the SIM card in X, Y and Z direction
- Card is typically located inside the device shell. Consumer must open the device shell to extract the card, and must insert and eject card manually
- Full single clip, provides shielding, and prevents card bending. This ensures a stable connection with all card types
- Components underneath the SIM card are possible (optional)




Block Type

- Basic SIM Connector without enhanced features in combination with an efficient manufacturing process leads to an extremely cost-effective component
- Anti-lifting contact prevents the contact from being accidentally lifted. Reduces the risk of damaged contacts
- Five (5) directional mating allows for card insertion from five directions: front, back, left, right and top. It thereby allows for maximum design freedom



Push-Push Type

- Push to insert, push to eject mechanism provides enhanced card handling for the end user
- Push-Push type connectors are typically used under the battery cover or behind a door at the device exterior
- The card detection switch senses card removal
- The connector prevents for reversed card insertion, eliminating damage done by wrong card insertion



Tray Type

- Tray type SIM connectors are typically used on the exterior of a device. The tray forms a unity with the device covers
- Tray can be fully separated from the body, allowing for easy card handling by the end user
- Fully-shielded, preventing EMI or other disturbances
- The connector prevents reversed card insertion, eliminating damage done by wrong card insertion
- The card detection switch senses card removal

Connectors for Mini SIM (2FF) Cards

P/N	Picture	Height range	Length × width	Description	Features and benefits	Status
-2042647-		1.8 – 2.0	15.5 x 10	Scalable shielded SIM	Features - shielded - holes for additional components under the connector - test holes for automatic inline testing Benefits - shield protects against radio interference - holes under the connector save space - test holes reduce applied costs	MP SH/India
-2042920-		1.8 – 2.0	15.5 x 10	Narrow shield version		MP SH/India
1981898-1		1.43	17.5 x 16.3	Super low profile SIM	Features - fully shielded - test holes - super low height contact - super low height Benefits - shield protects against radio interference - test holes reduce applied costs - can only be engaged from one side	MP SH
1932669-2		2.05	26.3 x 14.7	Side entry SIM connector LEFT Side entry SIM connector RIGHT	Features - visible detection of wrong card insertion - chamfered housing - user friendly shield design - test holes Benefits - prevents wrong card insertion - safe user handling - can remove card without tools - shield prevents EMI - inline testing reduces costs	MP SH
1551956-1		1.4	15.5 x 14.25	SIM 1.4mm height	Features - provides card stop - shielded - preloaded contacts - holes under the connector - test holes Benefits - card stop prevents damage to the SIM card - shield prevents EMI, RF distortion and card bend - preloaded anti-lifting contacts protect card from abuse - mounting components under the connector saves space - automated testing reduces costs	MP GD
1932766-1		1.5	17.6 x 16.1	SIM 1.5mm height		MP GD
1932768-1		1.95	16.3 x 14.8	Super low profile SIM with flange (big shield)	Features - one clip type (bridge type) - shielded - holes under the connector - card stop and guide - preloaded contacts - test holes Benefits - prevents card damage - shield prevents EMI, RF distortion and card bend - preloaded anti-lifting contacts protect card from abuse - mounting components under the connector saves space - automated testing reduces costs	MP SH

Push-Pull Type

(dimensions:mm)


Connectors for Mini SIM (2FF) Cards

	P/N	Picture	Height range	Length x width	Description	Features and benefits	Status
Block Type	*-1705300-*		1.5 - 2.8	10 x 7.6	5-Directional SIM connector	Features <ul style="list-style-type: none"> - 5 insert directions - preloaded contacts - fits both standards (2FF and 3FF) Benefits <ul style="list-style-type: none"> - smooth insertion for consumer - design flexibility 	MP QD
Push - Push Type	1981959-1		1.87	23.7 x 18.9	Push-push SIM connector	Features <ul style="list-style-type: none"> - push-push function - card detection switch - fully shielded - anti launch mechanism - test holes Benefits <ul style="list-style-type: none"> - prevents inaccurate switch readings caused by common rough edges on cards - shield prevents EMI RF distortion and card bend - prevents wrong card insertion - prevents card going airborne when extracted - automated testing reduces costs 	MP SH
	2174918-1		1.40	26 x 17	Push-push SIM, super low profile	Features <ul style="list-style-type: none"> - push-push function allows SIM card ejection by connector itself - lower profile - dual slanted contacts - card detection switch Benefits <ul style="list-style-type: none"> - easy to handle SIM card - low profile saves PCB space - dual slanted contacts provide strong mating force and avoid contact jam - card detection switch secures circuit design 	MP GD
Tray Type	2134033-1		1.4	25.85 x 16.7	Double contact metal tray	<ul style="list-style-type: none"> - tray can be fully separated from the body, allowing for easy card handling by the end user 	MP JP
	2134034-1				Double contact body assy		MP JP

(dimensions:mm)

Connectors for Micro SIM (3FF*) Cards

Size comparison : Mini SIM (2FF) vs Micro SIM (3FF)



Pad layout is identical



*FF : Form Factor

Mini SIM/2FF

25L x 15W (375mm²)

Micro SIM/3FF

15L x 12W (180mm²)

	P/N	Picture	Height range	Length x width	Description	Features and benefits	Status
Push-Push Type	2174803-2		1.27	15.98 x 15.1	Ultra low profile push-push	<ul style="list-style-type: none"> - push-push function allows SIM card ejection by connector itself to help the end customer handle SIM card easily - avoid card insertion with wrong direction, avoid card jamming issue - low profile saves space - dual slanted contacts provide strong mating force and avoid contact jam - card detection switch secures circuit design 	MP SH
Push-Pull Type	2108431-3 (8 position)		1.24	14.1 x 13.3	Ultra low profile push-pull	<ul style="list-style-type: none"> - low profile saves space - card detect switch uniquely integrated on connector contacts to better secure circuit connection while not taking extra PCB space - avoid card insertion with wrong direction - 6 position is optional - card stop confirms full insertion to the user - inspection holes allow customers to inspect solder connection 	MP SH
	2199337-5 (8 position)		1.18		Anti-buckling ultra low profile push-pull	<ul style="list-style-type: none"> - the lowest profile in the market enables slimmer application - the new contact design prevents buckling in use of a nano-SIM card to an adaptor - compatible pattern allows you to switch from H1.24 to H1.18 easily 	MP SH
Combo Type Connector for Micro SIM + MicroSD™	2199003-2		2.5	17.75 x 14.0	Micro SIM + micro SD combo	<ul style="list-style-type: none"> - dual card reader Micro SIM/Micro SD type, space saving design - transverse card orientation - push-pull type - micro SD card retention feature - micro SD detect switch - pick and place design on shell 	MP GD

(dimensions:mm)

Frequently Asked Questions

Question 1

How do I decide which type of SIM connector to choose?

Answer 1

The major difference in choosing between SIM connectors depends on the design of the customer device. Push-push or tray type SIM connectors allow users to extract the SIM card from the external portion of the device. Push-pull or block type connectors require users to open the back shell of the device and manually pull out the SIM card.

Question 2

What is the purpose of an 8 position SIM connector?

Answer 2

The extra two positions support an additional function like e-Pay.

Question 3

What is the benefit of dual-slanted contact performance?

Answer 3

The dual-slanted design prevents contact jam issues and creates a stronger mating performance, as demonstrated during the drop test.

Question 4

When should I use a micro SIM connector?

Answer 4

When the device requires the use of a micro SIM card.

Question 5

What's the scalable height?

Answer 5

The scalable height is found when the SIM card connector is scalable by a different P/N, but the connector footprint stays the same. The benefit is enabling the customer to swap the product easily when a design change occurs, thereby reducing the lead-time of TTM (Time To Market), TTV (Time To Value) and design cost.

FOR MORE INFORMATION

TE Connectivity Technical Support Center

USA: +1 (800) 522-6752
Canada: +1 (905) 475-6222
Mexico: +52 (0) 55-1106-0800
Latin/South America: +54 (0) 11-4733-2200
Germany: +49 (0) 6251-133-1999

UK: +44 (0) 800-267666
France: +33 (0) 1-3420-8686
Netherlands: +31 (0) 73-6246-999
China: +86 (0) 400-820-6015

Part numbers in this brochure are RoHS Compliant*, unless marked otherwise.

*as defined www.te.com/leadfree

te.com

©2014 TE Connectivity Ltd. family of companies. All Rights Reserved.

2-1773464-0 SPARKS 07/2014

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.